



公差表 (General tolerances)(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±1.05	±1.93
±1.15	±1.60
±2.20	±2.50
0.1/10	±Z

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
SIZE: A4	mm / inch
DRAWING NO.:	SA635-6.35-XXP-1Y-00A(H)
SCALE:	1/1

宁波三安电子科技有限公司
 Sanan Electrical Technology Co. Ltd

ITEM	NAME OF PART	MATERIAL	NOTES
4	Pin Header	Copper	Sn Plated
3	Screw	Steel	M3/Zn Plated
2	Cage	Copper Alloy	M3/Ni Plated
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电压 / Rated Voltage(V)/Current(A)	300/30	/	300/10
EC 标准 / EC Standard:			
额定电压/电压 / Rated Voltage(V)/Current(A)	450/32		
工额定电压 / Withstanding Voltage(V/1MIN)	AC2500		
螺栓扭矩 / Torque Tightening(N·m/Lb.in)	M3: 0.5/4.43		
线径范围 (硬线和软线) / Wire Range(rigid and flexible)(mm ² /AWG)	1.5~4/26~10		
可焊/Pitch(mm) / 线径范围 / Poles	6.35/N=02~24P		
使用温度范围 / Operating temperature(°C)	-40~+105		
符合RoHS环保要求 / Conform to RoHS	Yes		