



ITEM	NAME OF PART	MATERIAL	NOTES
6	Screw 2	Steel	M2.5/Zn Plated
5	Screw 1	Steel	M2/Zn Plated
4	Cage	Copper Alloy	M2/Ni Plated
3	Clamp	Copper Alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/8	/	300/8
EC 标准 / EC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	II/2		
额定电压/电流 / Rated Voltage(V)/Current(A)	250/7		
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)	2.5		
扭矩 / Torque / Tightening (N·m/Lb.in)	M2: 0.2/1.77		
导线范围 (硬线和软线) / Wire Range (rigid and flexible) (mm ² /AWG)	0.5~1.5 / 28~16		
剥线长度 / Stripping length (mm)	3.81 / N=02~24P		
使用温度范围 / Operating temperature (°C)	-40~+105		
符合RoHS环保要求 / Conform to RoHS	Yes		

SURFACE:

 **宁波三安电子科技有限公司**
Sanan Electrical Technology Co., Ltd

NAME: **ZESAKM-3.81-XXP-1Y-00A(H)**

DRAWING NO.: **ZESAKM-3.81-XXP-1Y-00A(H)**

SCALE: **1/1**

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
SIZE: A4	
mm / inch	
TYPE:	

公差 (General Tolerances) (mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
±Z	±0.1/10	±0.15	±0.2	±0.3	±0.4	±0.5	±0.6	±0.8	±1.0	±1.2	±1.5	±2.0	±2.5	±3.0

公差 (General Tolerances) (mm)	±Z
------------------------------	----