



公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10					
~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z					
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50						

MATERIAL:		SURFACE:	
MAT NO.:			
STATUS:			
APPD:			
CHKD:			
DRAFT:			
NAME:	宁波三安电子科技有限公司 Sanan Electrical Technology Co. Ltd		
DRAWING NO.:	15ESAKNHM-3.5-XXP-1Y-00A(H)		
TYPE:	SCALE:	SHEET	REV
		1/1	

ITEM	NAME OF PART	MATERIAL	NOTES
6	Screw	Steel	N/2/Zn Plated
5	Spring	Stainless steel	
4	Clamp	Copper alloy	Sn Plated
3	Button	POM	UL94HB
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/8	50/8	/
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等级/ Pollution Degree	III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)	200/9.5	250/9.5	320/9.5
额定脉冲电压 (KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5
线径范围 (硬线和软线)/Wire Range(rigid and flexible)(AWG/rmm ²)	26~16/0.2~1.5		
间距/Pitch(mm)/线数范围/Poles	3.50/N=04~48P		
剥线长度/Stripping length(mm)	10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		